

4




3

2

1

REVISION DATA

REV	DESCRIPTION	DATE
A0	NEW DRAWING	2011-04-21



Technical Data

Material:

Contact Material: Brass

Contact plating: Au or Sn Over 50μ" Ni

Insulator Material: Black Polyester UL94V-0

Standard: PBT/PA6T+30%G.F

Electrical:

Current rating: 2.0Amps/contact max.

Contact resistance: ≤20mΩ/contact

Insulation resistance: ≥1000MΩ at V=100V

Withstanding Voltage: 1000V AC/minute


Mechanical:

Mechanical life cycle: min.200

Operating temperature: -40°C to +105°C

Soldering temperature: +255°C

包装方式: 袋装



P.C.B LAYOUT

Dimension antitheses list (尺寸选型表)

Item (项目)	L	PA	PC	H
Standard (尺寸)				
Remarks (备注)	以上尺寸可由客户选择			

PZ	2	XX	11	XXX	D	XX	X	N	N	XXX
品名 PZ=排针	间距 2=2.00	塑高 10=1.00mm 15=1.50mm 20=2.00mm	产品类型 11=单塑单排	PIN位总数 01~40P	产品折弯类型 D=直插	表面处理 SN=1in120u" W=镀镍 G1=Gold Flash G2=Gold 1u" G3=Gold 2u" G4=Gold 3u" G5=Gold 5u" G6=Gold 10u" G7=Gold 15u" G8=Gold 30u" GA=Gold 1.5u" S0=半金锡	塑胶材质 A=PBT B=PA46 C=PA6T D=PA66 E=PA9T F=LCP	塑胶特性 N=常规	排针盖 N=无	针长 针长= 1.0+PC+PB +H+PA

nicetycomm 深圳市创辉诚科技有限公司
SHENZHEN CHUANGHUICHENG TECHNOLOGY CO.,LTD

TOLERANCE	PROJECTON	TITLE:
ANGLE ±5°	DATE: 2011-04-21	单排单塑180度排针 PH2.00 系列图
X.XXX ±0.10	DRAWN:	PART NO: PZ2XX11XXXDXXXNXXX
X.XX ±0.20	CHECKED:	DRAWING NO: PZ2XX11DXXX024
X.X ±0.30	APPROVED:	REV: A0 UNIT: mm SCALE: 4:1 SIZE: A4
X. ±0.50		